

SIGNAL CLAMP

The Signal Clamp provides a safe and straightforward way to apply the Generator/ Transmitter signal to a cable or small pipe to enable precision tracing of this service.

The C.SCOPE Signal Clamp allows operators to apply the Generator/ Transmitter signal from any C.SCOPE Signal Generator or Transmitter effectively to any cable. It is an extremely practical way to allow individual cables to be traced even when the cable is in amongst other cables.



Signal Clamp SPECIFICATION

| | |
|---------------|--|
| Product Name | Signal Clamp |
| Part No. | YIRC-33-8 |
| Construction | Toroidal induction ring housed in robust plastic Spring loaded jaws |
| Frequency | Tuned for optimum use with 33kHz Signal Generators/ Transmitters |
| Dimensions | 270 x 160 x 28 mm (10.6" x 6.3" x 1.1") |
| Lead length | 2 m (6'6.7") |
| Compatibility | Maximum cable diameter 105 mm (4.1") Suitable for use with all C.Scope Signal Generators and Transmitters |
| Safety | Built to conform to BSEN61010-1:1993 and BSEN 61010-2-032:1995 |
| IP Rating | 54 |

Specification subject to change without notice.

C.SCOPE

C.SCOPE International Ltd

Kingsnorth Technology Park Wotton Road Ashford Kent TN23 6LN United Kingdom
Telephone +44(0)1233 629181 Fax +44(0)1233 645897 email info@cscope.co.uk

www.cscopelocators.com

All C.SCOPE products are manufactured under a quality system accredited to ISO9001:2008



The information in this leaflet is believed to be correct at time of going to press. C.SCOPE International reserve the right to change prices at any time without prior notice.